



DURATA LINE 20-840-2420LM FL Special Edition



Technical Details:

Luminous Flux:	2420 lm
LED Output:	19 W
Light Yield:	121 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	70 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 200-240V, 50/60Hz, DC 32-42V
Power Consumption:	20 W
Driver Manufacturer:	Boke
Power Factor (PF):	>0.95
Input Driver:	plug connector
Output of Driver:	DC 30-40V, 900mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-30°C - 60°C

Dimensions:	990x50x95 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	20
IK Code:	07
Housing Color	white
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	modular
Cover:	frost mit Raster
Net Weight:	1920 g
Type of Packaging:	box
Dimensions of Packaging:	1000x60x105
Weight incl. Packaging:	2.071 kg
Content Master Package:	8
Dimensions of Master Package:	1020x265x245 mm
Weight Master Package:	18,5 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405219090
Certifications	CE
Barcode:	4250557825069
Elegante, modulare Lichtlinienleuchte für Büros	
400cm Zuleitung mit 3-Phaseadapter white	
Für Bildschirmarbeitsplätze geeignet	
Stahlseilabhängung 1,5 oder 3m optional erhältlich	
oder Montage mediums Deckenclipse	

Information and Downloads:

