

LED- ASTARA 15-38/927/1950-4750LM BK max. 130lm/W



Product information "LED- ASTARA 15-38/927/1950-4750LM BK max. 130lm/W"

LED-Trackspot

- high efficient LED-Spot max. 130lm/W 1950-4730lm
- for common 3 Phase Trackrails, also in Dali Version available
- high reflective Alanod segment reflector
- compact in track driver with output select: 300-1050mA, 15-38W using range, ENEC05 certified
- long lifespan components guarantee low maintenance and operational costs
- compact construction with wide swivel range
- exchangeable reflector with different beam angles as an option: 15° and 24°

Applications:

- Shops, supermarket, showroom
- Museum, gallery, exhibition

Technical Details:

Luminous Flux	4730 lm
Light Yield:	124 lm/W
Light Temperature:	2700 K
Color Rendering Index (CRI)	≥90 Ra
Color Consistency (SDCM):	3
Power Consumption:	12-38 W
Power Factor (PF):	0.95
Operating Hours:	>50.000 h L80/B10
Switching Cycles:	>100.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-10°C - 40°C
Housing Material:	aluminum
Housing Color	white
Coating:	powder-coated
Pivot Range pan:	355 °
Pivot Range tilt:	90 °
Dimensions	90x108 mm
Warranty	5 years

Information and Downloads:

