Technical Data Sheet

Order number: LG40245

LITEGEAR
LED Lighting Solutions

Yola Brick Wall Light 200-10W-CCT Select BK 700lm Triac Dim IP65

Technical Details:

Luminous Flux:	700 lm
Light Yield:	70 lm/W
Light Temperature:	2700,3000,4000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<5
Light Emission:	
Dimmable:	✓
Method of Dimming:	"Triac Phasenan-/abschnitt"
LED-Chip:	SMD 2835
Ignition Time:	<1 s
Power Consumption:	10 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	Terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 60°C

Dimensions:	200x100x60 mm
Mounting:	Wand
Montageart:	surface mounted
IP Class:	65
IK Code:	03
Housing Color	black
Housing Color (RAL Code):	similar 9005
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	Glasabdeckung oben unten
Cover:	frosted
Net Weight:	710 g
Type of Packaging:	box
Dimensions of Packaging:	220x125x80
Weight incl. Packaging:	0.987 kg
Content Master Package:	12
Dimensions of Master Package:	455x270x260 mm
Weight Master Package:	11,93 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE
Barcode:	4250557823560

Direkte und indirekte Ausleuchtung sep. schaltbar

Farbwahlschalter CCT-Select: 2700K, 3000K, 4000K

Abstrahlwinkel: 115° x 60° (40° asym. nach vorne)

dekorative Wandleuchte für kreative Lichtspiel

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de