

Xona Maxima Basic Unit 150WFL 50-840-8600LM DALI DIM



Technical Details:

Luminous Flux:	8600 lm
LED Output:	51 W
Light Yield:	172 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	140 °
Unified Glare Rating (UGR):	<24
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI,Push-Dim
LED-Chip Manufacturer:	Epistar
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 180-264V, 330mA, 50/60Hz, DC 170-230V
Power Consumption:	Power Select (35, 40, 45, 50 W)
Contains Driver:	✓
Driver Manufacturer:	Litegear
Power Factor (PF):	>0.96
Input Driver:	terminal
Output of Driver:	DC 55-80V, 620mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓

Dimensions:	1498,5x70x39,4 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	30
IK Code:	02
Housing Color	white
Housing Material:	steel
Coating:	coated
Special Feature of Housing:	geringe Blendung opal
Cover:	opal
Net Weight:	1630 g
Type of Packaging:	none
Weight incl. Packaging:	1.63 kg
Content Master Package:	10
Dimensions of Master Package:	1570x400x210 mm
Weight Master Package:	19,8 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	65.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,ENEC,LM80,CB
Power Select und Dali 2.0 Dim	

Storage Temperature:

-40°C - 60°C

Information and Downloads:

