
Technical Data Sheet

Order number: LG30225PS

LITEGEAR
LED Lighting Solutions

Velostra Line 1500 30/60-840-4200/8400LM







Technical Details:

Luminous Flux:	8400 lm
Light Yield:	140 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<5
Beam Angle:	120 °
Unified Glare Rating (UGR):	<24
Light Emission:	downward
LED-Chip Manufacturer:	Everlight
LED-Chip:	SMD 2835
Number of LED:	144
Ignition Time:	<0,5 s
Input Current:	AC 200 - 240V, 280/560mA, 50/60Hz
Power Consumption:	Power Select (30, 60 W)
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	cable with plug
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-10°C - 40°C
Storage Temperature:	-20°C - 55°C

Dimensions:	1498x46x65,5 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	20
IK Code:	08
Housing Color	Alu
Housing Material:	aluminum
Special Feature of Housing:	PC Cover
Cover:	opal
Net Weight:	820 g
Type of Packaging:	bag
Weight incl. Packaging:	0.88 kg
Content Master Package:	6
Dimensions of Master Package:	1640x188x160 mm
Weight Master Package:	5,770 kg
Product Line:	Essential Line
Warranty	3 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	94054239
Certifications	CE,TÜV,LM80
Barcode:	4250557824635
Einfache, und schnelle Montage	
LED-Modul für Tragschiene	
Power Select 30/60W max. 140lm/W	

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de