

Kompakter Driver für Panel und Downlights



Technical Details:

Method of Dimming:	1-10V
Input Current:	AC 198-264V, 180mA, 50/60Hz, DC 180-280V
Power Consumption:	36 W
Driver Manufacturer:	KGP
Power Factor (PF):	>0.92
Input Driver:	terminal
Output of Driver:	DC 10-50V, 150-900mA
CC/CV:	CC
Output Current Adjustable:	✓
Electrical Protection Class:	II
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 50°C
Storage Temperature:	-20°C - 90°C

Dimensions:	128x30x21 mm
Montageart:	recessed
IP Class:	20
Housing Color	white
Housing Material:	plastic
Special Feature of Housing:	ohne Zuentlastung
Net Weight:	119 g
Weight incl. Packaging:	0.125 kg
Content Master Package:	120
Weight Master Package:	12,56 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h
Certifications	CE,ENEC,SELV
Power Select: 320-1050mA, 50mA steps	
perfect for LED panels and downlights	
max. driver on 16A breaker: B Type: 21,C Type: 35	

Information and Downloads:

