

# Modulux Linear LED- Modul 150-35/50-940-7500lm-WH



## Technical Details:

|                            |                                 |
|----------------------------|---------------------------------|
| Luminous Flux:             | 7500 lm                         |
| LED Output:                | 48 W                            |
| Light Yield:               | 150 lm/W                        |
| Light Temperature:         | 4000 K                          |
| Light Color:               | neutralwhite                    |
| Color Rendering Index:     | ≥90 Ra                          |
| Color Consistency (SDCM):  | <4                              |
| Beam Angle:                | 90 °                            |
| Light Emission:            | downward                        |
| LED-Chip:                  | SMD 2835                        |
| Ignition Time:             | <0,5 s                          |
| Input Current:             | AC 220 - 240V, 50/60Hz          |
| Power Consumption:         | Power Select (35, 40, 45, 50 W) |
| Contains Driver:           | ✓                               |
| Power Factor (PF):         | >0.95                           |
| Input Driver:              | lighting track                  |
| Output of Driver:          | DC 55-80V, 710mA                |
| CC/CV:                     | CC                              |
| Output Current Adjustable: | ✓                               |
| Input Lamp:                | Power rail                      |
| Switching Cycles:          | >100.000                        |
| Ambient Temperature (TA):  | -20°C - 45°C                    |
| Storage Temperature:       | -20°C - 55°C                    |

|                                                   |                     |
|---------------------------------------------------|---------------------|
| Dimensions:                                       | 1490x60x11 mm       |
| Mounting:                                         | Decke, Stromschiene |
| IP Class:                                         | 20                  |
| IK Code:                                          | 03                  |
| Housing Color                                     | white               |
| Housing Material:                                 | aluminum            |
| Coating:                                          | powder-coated       |
| Special Feature of Housing:                       | 3-Phase adapter     |
| Cover:                                            | Lens                |
| Net Weight:                                       | 1150 g              |
| Type of Packaging:                                | none                |
| Weight incl. Packaging:                           | 1.15 kg             |
| Content Master Package:                           | 10                  |
| Dimensions of Master Package:                     | 1570x350x240 mm     |
| Weight Master Package:                            | 14,55 kg            |
| Product Line:                                     | Advance Line        |
| Warranty                                          | 4 years             |
| Operating Hours:                                  | 50.000 h L80/B10    |
| Disposal Obligation:                              | ✓                   |
| Customs Tariff Number:                            | 9405119090          |
| Certifications                                    | CE, TÜV             |
| Barcode:                                          | 4250557824376       |
| Spezial Optik für Supermarktregale optional       |                     |
| optional optics for shelf lighting in supermarket |                     |
| 90° symmetric                                     |                     |
| Power adjust: 35/40/45/50W 5300-7500LM max.       |                     |
| High CRI für beste Farbwiedergabe                 |                     |

Information and Downloads:

