Product Information

**Order number: LG32277BK**

# Modulux Linear LED- Modul 150-35/50-940-7125lm-BK





## Technical Details:

| | |
|---|---|
| **Luminous Flux** | 7125 lm |
| **Light Yield:** | 143 lm/W |
| **Light Temperature:** | 4000 K |
| **Color Rendering Index (CRI)** | ≥90 Ra |
| **Color Consistency (SDCM):** | 4 |
| **Power Consumption:** | 35, 40, 45, 50 W |
| **Power Factor (PF):** | 0.95 |
| **Operating Hours:** | >50.000 h L80/B10 |
| **Switching Cycles:** | >100.000 |
| **Ignition Time:** | <0,5 s |
| **Ambient Temperature (TA):** | -20°C - 45°C |
| **Housing Material:** | aluminum |
| **Housing Color** | black |
| **Coating:** | powder-coated |
| **Dimensions** | 1490x60x11 mm |
| **Net Weight:** | 1150 g |
| **Warranty** | 5 years |

Information and Downloads:

## Product information "Modulux Linear LED- Modul 150-35/50-940-7125lm-BK"

Linear LED tracklight for 3-phase trackrails
high CRI

Elegant, flat LED luminaire with integrated 3-phase track adapter which is completely integrated in the standard track rails. Elegant, ultra flat appearance only 11mm high and 60mm wide. Available with symmetrical 60/90/120° or asymmetrical light dispersion 2 x 45° with multi-lens panel. Ideal for illuminating supermarket shelves, retail areas, exhibition halls, extremely high luminous flux up to 8000 lumens with only 50W consumption corresponding to up to 160 lumens / watt.

- Easy and fast installation using 3-phase trackrail adapters.
- 3 selectable power phases, compatible with all common track systems
- Adjustment output power: Adjustable LED driver 35, 40, 45, 50Watt
- Modular structure of the lens panel
- The individual modules can be seamlessly lined up. It creates the impression of a continuous line of light.
- Good heat dissipation and optimal light distribution
- Also available with dimmable Dali driver on request.
- Available in 2 housing colors: black, white optional also in silver (clarify minimum quantity beforehand)

5000K, 6000K
- available in two lengths: 60cm and 150cm