


Modulux WING Linear LED- Modul 150-35/50-940-7500lm-WH



3-phasen Stromschiene

Technical Details:

Luminous Flux:	7500 lm
LED Output:	60 W
Light Yield:	150 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥90 Ra
Color Consistency (SDCM):	<4
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 150mA, 50/60Hz
Power Consumption:	50 W
Contains Driver:	✓
Power Factor (PF):	>0.95
Input Driver:	lighting track
Output of Driver:	DC 55-80V, 710mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Power rail
Switching Cycles:	>100.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-25°C - 60°C
Storage Temperature:	-40°C - 85°C

Dimensions:	1500x120x12 mm
Mounting:	Decke, Stromschiene
IP Class:	20
IK Code:	03
Housing Color	white
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	3-Phase adapter
Cover:	Linse + Frost
Net Weight:	2150 g
Type of Packaging:	none
Weight incl. Packaging:	2.15 kg
Content Master Package:	10
Dimensions of Master Package:	1570x430x330 mm
Weight Master Package:	24,8 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	60.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE, TÜV
Barcode:	4250557823928
spezielle Optik für Supermarktregale	
special optics for shelf lighting in supermarkets	
2 x 90° x 30° double asymmetric + 90° down prism.	
Power adjust: 35/40/45/50W 5320-7500LM max.	

Information and Downloads:

