

# Modulux Linear LED- Modul 60-14/20-930-2880lm-WH



## Technical Details:

|                              |                               |
|------------------------------|-------------------------------|
| Luminous Flux:               | 2880 lm                       |
| LED Output:                  | 19 W                          |
| Light Yield:                 | 144 lm/W                      |
| Light Temperature:           | 3000 K                        |
| Light Color:                 | warmwhite                     |
| Color Rendering Index:       | ≥90 Ra                        |
| Color Consistency (SDCM):    | <4                            |
| Beam Angle:                  | 90 °                          |
| Light Emission:              | downward                      |
| LED-Chip:                    | SMD 2835                      |
| Ignition Time:               | <0,5 s                        |
| Input Current:               | AC 220 - 240V, 150mA, 50/60Hz |
| Power Consumption:           | 20 W                          |
| Contains Driver:             | ✓                             |
| Power Factor (PF):           | >0.95                         |
| Input Driver:                | lighting track                |
| Output of Driver:            | DC 55-80V, 280mA              |
| CC/CV:                       | CC                            |
| Output Current Adjustable:   | ✓                             |
| Input Lamp:                  | Power rail                    |
| Switching Cycles:            | >100.000                      |
| Electrical Protection Class: | I                             |
| Ambient Temperature (TA):    | -25°C - 60°C                  |
| Storage Temperature:         | -40°C - 85°C                  |

|                                                    |                     |
|----------------------------------------------------|---------------------|
| Dimensions:                                        | 600x60x11 mm        |
| Mounting:                                          | Decke, Stromschiene |
| IP Class:                                          | 20                  |
| IK Code:                                           | 03                  |
| Housing Color                                      | white               |
| Housing Material:                                  | aluminum            |
| Coating:                                           | powder-coated       |
| Special Feature of Housing:                        | 3-Phase adapter     |
| Cover:                                             | Lens                |
| Net Weight:                                        | 550 g               |
| Type of Packaging:                                 | none                |
| Weight incl. Packaging:                            | 0.55 kg             |
| Content Master Package:                            | 10                  |
| Dimensions of Master Package:                      | 670x350x240 mm      |
| Weight Master Package:                             | 7,8 kg              |
| Product Line:                                      | Advance Line        |
| Warranty                                           | 5 years             |
| Operating Hours:                                   | 50.000 h L80/B10    |
| Disposal Obligation:                               | ✓                   |
| Customs Tariff Number:                             | 9405119090          |
| Certifications                                     | CE, TÜV             |
| Barcode:                                           | 4250557824406       |
| optional spezial Optik für Supermarktregale        |                     |
| optional optics for shelf lighting in supermarkets |                     |
| 90° symmetric                                      |                     |
| Power adjust: 14/16/18/20W 2100-3000LM max.        |                     |

Information and Downloads:



