

Modulux Linear LED- Modul WF-60-14/20-940-2780lm-WH



Technical Details:

Luminous Flux:	2780 lm
LED Output:	19 W
Light Yield:	139 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥90 Ra
Color Consistency (SDCM):	<3
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Power Consumption:	20 W
Contains Driver:	✓
Driver Manufacturer:	Litegear
Power Factor (PF):	>0.95
Input Driver:	lighting track
Output of Driver:	DC 55-80V, 280mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Power rail
Switching Cycles:	>100.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-25°C - 60°C
Storage Temperature:	-40°C - 85°C

Dimensions:	600x60x12 mm
Mounting:	Decke, Stromschiene
IP Class:	20
IK Code:	03
Housing Color	white
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	3-Phase adapter
Cover:	frosted
Net Weight:	550 g
Type of Packaging:	none
Weight incl. Packaging:	0.55 kg
Content Master Package:	10
Dimensions of Master Package:	670x350x240 mm
Weight Master Package:	7,8 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	60.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE, TÜV
Barcode:	4250557823874
optional spezial Optik für Supermarktregale	
optional optics for shelf lighting in supermarkets	
120° symmetric	
Power adjust: 14/16/18/20W 2100-3060LM max.	
30°seitlich schwenkbar	

Information and Downloads:

