



Cappila POULTRY 1150 30-RED-840-3900lm internal wire through terminals



Technical Details:

Luminous Flux:	3900 lm
LED Output:	26 W
Light Yield:	130 lm/W
Light Temperature:	4000 + 625nm red K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	120 °
Unified Glare Rating (UGR):	<30
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	0-10V,1-10V
LED-Chip Manufacturer:	Hongli
LED-Chip:	SMD 2835
Number of LED:	216
Ignition Time:	<1 s
Input Current:	AC 200 - 240V, 50/60Hz
Power Consumption:	30 W
Contains Driver:	✓
Driver Manufacturer:	AIDimming
Power Factor (PF):	>0.97
Input Driver:	terminal
Output of Driver:	DC 9-42V, 300-750mA
CC/CV:	CC
Input Lamp:	Terminal
Switching Cycles:	>200.000
Electrical Protection Class:	I

Dimensions:	75x1152 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	67
IK Code:	10
Housing Color	white/silver
Housing Material:	Polycarbonat
Special Feature of Housing:	Tube
Cover:	opal
Net Weight:	2000 g
Type of Packaging:	box
Dimensions of Packaging:	1310x80x80
Weight incl. Packaging:	2.3 kg
Content Master Package:	6
Dimensions of Master Package:	1330x260x180 mm
Weight Master Package:	14 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	54.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405114090
Certifications	CE,LM80
Barcode:	4250557825298
Rohrleuchte	
Tube Light	
Edelstahlendkappen	
Durchgangsverdrahtung	

Storage Temperature:

-20°C - 60°C

Information and Downloads:

