Technical Data Sheet

Order number: LG14405W

TAGIRA UGR LINE 40-830-850-3600LM max.







Technical Details:

Luminous Flux:	4400 lm
Light Yield:	110 lm/W
Light Temperature:	3000, 4000, 5000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	80 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	"Power Select"
LED-Chip Manufacturer:	MTC
LED-Chip:	SMD 2835
Number of LED:	240
Ignition Time:	<0,5 s
Input Current:	AC 200-240V, 50/60Hz, DC 115-260V
Power Consumption:	Power Select (20, 30, 40 W)
Contains Driver:	✓
Driver Manufacturer:	Litegear
Power Factor (PF):	>0.9
Input Driver:	cable with flying leads
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Terminal
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-25°C - 45°C
Storage Temperature:	-40°C - 70°C

Dimensions:	1183x67x73 mm
Mounting:	Decke,Deckenabhängung
Montageart:	surface mounted
IP Class:	20
IK Code:	08
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	Stahlblech + plastic
Coating:	powder-coated
Special Feature of Housing:	Rasterleuchte
Cover:	frost mit Raster
Net Weight:	1135 g
Type of Packaging:	box
Dimensions of Packaging:	1195x75x82
Weight incl. Packaging:	1.31 kg
Content Master Package:	6
Dimensions of Master Package:	1210x165x270 mm
Weight Master Package:	8,6 kg
Product Line:	Essential Line
Warranty	3 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,LM80
Barcode:	4250557826394
Elegante, modulare Balkenleuchte für Büros	
Für Bildschirmarbeitsplätze geeignet	

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

