Product Information

Order number: LG5858

ORI-XL 32-830-850-3840LM-IP64









Product information "ORI-XL 32-830-850-3840LM-IP64"

LED wall - / Ceiling light OneFitAll

- CCT Select: 3000K, 4000K, 5000 Kelvin
- Power Select: 15W, 22W, 32W
- High system efficiency: 120lm/W 3840lm@ 32W 4000K
- timeless, mushroom design
- priliminaire weather and dust proof IP64
- compact housing
- applications: stoarage rooms, corridors, residential, bath room, outside under cannopies,
- easy installation

Technical Details:

Luminous Flux	3840 lm
Light Yield:	120 lm/W
Light Temperature:	3000, 4000, 5000 K
Color Rendering Index (CRI)	≥80 Ra
Color Consistency (SDCM):	4
Power Consumption:	15, 22, 32 W
Power Factor (PF):	0.9
Operating Hours:	>50.000 h L80/B10
Switching Cycles:	>30.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-20°C - 40°C
Housing Material:	steel
Housing Color	white
Coating:	lacquered
Dimensions	410x103 mm
Net Weight:	787 g
Warranty	3 years

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de