Technical Data Sheet

Order number: LG5858

ORI-XL 32-830-850-3840LM-IP64







Technical Details:

Luminous Flux:	3840 lm
LED Output:	21 W
Light Yield:	120 lm/W
Light Temperature:	3000, 4000, 5000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Light Emission:	downward
LED-Chip Manufacturer:	Zhaoyuan
LED-Chip:	SMD 2835
Number of LED:	56
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 50/60Hz, DC 172-250V
Power Consumption:	Power Select (15, 22, 32 W)
Contains Driver:	✓
Driver Manufacturer:	MOHO
Power Factor (PF):	>0.9
Input Driver:	terminal
Output of Driver:	DC 109-125V, 240mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Terminal
Switching Cycles:	>30.000
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-20°C - 40°C

Dimensions:	410x103 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	64
IK Code:	02
Housing Color	white
Housing Color (RAL Code):	similar 9003
Housing Material:	steel
Coating:	lacquered
Special Feature of Housing:	PMMA cover
Cover:	opal
Net Weight:	787 g
Type of Packaging:	box
Dimensions of Packaging:	450x450x113
Weight incl. Packaging:	1.121 kg
Content Master Package:	5
Dimensions of Master Package:	600x450x457 mm
Weight Master Package:	7 kg
Product Line:	Essential Line
Warranty	3 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE
Barcode:	4250557825533
Power Select und CCT Select	
weiche, gleichmäßige Ausleuchtung	

Information and Downloads:

