

Lunara Smart 100-CCT-Select-12000LM IP66 IK08 GEG



Product information "Lunara Smart 100-CCT-Select-12000LM IP66 IK08 GEG"

LUNARA SMART: LED Floodlight with CCT- and Power-Select prepared for optional Motion Sensor

- Ultra compact, flat DOB LED-Flood light including IR-remote
 - CCT-Select: light colour selectable vis IR remote: 2400K, 3000K, 4000K
 - Power Select: power adjustment via IR remote: 50W, 70W, 100W
 - optional plug `n play IR Sensor, refer to accessories
 - 4mm tempered glass, weather proof housing IP66, IK08 with mounting bracket and feed in cable
 - air compensation valve
-
- 35cm rubber cable 3 x 1,0mm² black
-
- incl. IR remote controller which will be used for the optional Sensor as well.

Applications:

garden, home, terrace, balcony, shad, warehouse, garage, walkway, architectural, farm

Technical Details:

Luminous Flux	12200 lm
Light Yield:	122 lm/W
Light Temperature:	2400, 3000, 4000 K
Color Rendering Index (CRI)	≥70 Ra
Color Consistency (SDCM):	5
Power Consumption:	50, 70, 100 W
Power Factor (PF):	0.9
Operating Hours:	>50.000 h L80/B10
Switching Cycles:	>50.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-20°C - 45°C
Housing Material:	aluminum
Housing Color	black
Coating:	powder-coated
Pivot Range tilt:	90 °
Dimensions	225x185x36 mm
Net Weight:	1180 g
Warranty	3 years

Information and Downloads:

