


Lunara Smart 50-CCT-Select-6000LM IP66 IK08 GEG



Technical Details:

Luminous Flux:	6100 lm
Light Yield:	122 lm/W
Light Temperature:	2400, 3000, 4000 K
Light Color:	CCT Select
Color Rendering Index:	≥70 Ra
Color Consistency (SDCM):	<5
Beam Angle:	120 °
Unified Glare Rating (UGR):	<25
Light Emission:	
Dimmable:	✓
Method of Dimming:	"Power Select"
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD 2835
Number of LED:	156
Ignition Time:	<0,5 s
Input Current:	AC 200 - 240V, 50/60Hz
Power Consumption:	Power Select (25, 37, 50 W)
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	cable with flying leads
Output Current Adjustable:	✓
Input Lamp:	cable with flying leads
Switching Cycles:	>50.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 70°C

Dimensions:	165x137x32 mm
Mounting:	ceiling,wall,ground
Mountingart:	surface mounted
Pivot Range tilt:	90 °
IP Class:	66
IK Code:	08
Housing Color	black
Housing Color (RAL Code):	similar 9005
Housing Material:	aluminum
Coating:	powder-coated
Cover:	clear
Net Weight:	680 g
Type of Packaging:	box
Weight incl. Packaging:	0.73 kg
Content Master Package:	20
Dimensions of Master Package:	360x210x330 mm
Weight Master Package:	15,4 kg
Product Line:	Essential Line
Warranty	3 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405421000
Certifications	CE,ERP
Barcode:	4250557825106
4mm Verbundglasscheibe	
4mm tempered glass cover	
inkl. IR Fernbedienung for CCT- und Power-Select	
incl. IR remote for CCT - and power select	
106-125lm/W	

Information and Downloads:

