


# Axea L 6-20-930-2180LM max. 106lm/W



## Technical Details:

Luminous Flux:	2180 lm
LED Output:	20 W
Light Yield:	106 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥90 Ra
Color Consistency (SDCM):	<3
Beam Angle:	38 °
Swappable Reflector:	✓
Light Emission:	downward
LED-Chip Manufacturer:	JUN CAN
LED-Chip:	COB
Number of LED:	1
Ignition Time:	<0,5 s
Power Consumption:	20 W
Contains Driver:	✓
Input Driver:	plug connector
Output of Driver:	DC 36V, 150-550mA
CC/CV:	CC
Input Lamp:	plug connector
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 60°C

Dimensions:	102x80 mm
Installation Depth:	70 mm
Cut-Out Dimensions:	90 mm
Mounting:	Decke
Montageart:	recessed
Pivot Range pan:	350 °
Pivot Range tilt:	80 °
IP Class:	20 (20 room side)
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Cover:	clear
Net Weight:	240 g
Type of Packaging:	box
Dimensions of Packaging:	455x410x400
Weight incl. Packaging:	0.296 kg
Content Master Package:	36
Dimensions of Master Package:	455x410x400 mm
Weight Master Package:	10,64 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B30
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557826011
Variablel Eingangsstrom:	150-550mA/6-20W
Sehr gute Farbwiedergabe	CRI>90Ra
System efficiency:	max. 106lm/W@12W

Information and Downloads:



