Technical Data Sheet

Order number: LG13300


LITEGEAR
LED Lighting Solutions


KITALPHA HighBay 80-830/840-11200LM GEG

















Technical Details:

Luminous Flux:	11200 lm
Light Yield:	140 lm/W
Light Temperature:	3000/4000 K
Light Color:	dualwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	1-10V
LED-Chip:	SMD 2835
Number of LED:	364
Ignition Time:	<0,5 s
Input Current:	AC 100-277V, 50/60Hz, DC 180-260V
Power Consumption:	Power Select (25, 40, 60, 80 W)
Contains Driver:	✓
Driver Manufacturer:	Lifud
Power Factor (PF):	>0.96
Input Driver:	cable with flying leads
Output of Driver:	DC 245V, 300mA
CC/CV:	CC

Dimensions:	230x290 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	20
IK Code:	06
Housing Color	grey
Housing Material:	aluminum
Coating:	powder-coated
Cover:	Lens
Net Weight:	1542 g
Type of Packaging:	box
Dimensions of Packaging:	350x270x270
Weight incl. Packaging:	2.028 kg
Content Master Package:	1
Dimensions of Master Package:	350x270x270 mm
Weight Master Package:	2,028 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,LM80
Barcode:	4250557826134

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-30°C - 45°C

without reflector
0-10V dimmable, Dali via oiptional Adapter
Power select: 25-80W
CCT select: 3000, 4000K

Information and Downloads: