


# CIELLA MEDI LED-Unit 15-827/840-WH 1650lm DALI DT6 IP44



## Technical Details:

Luminous Flux:	1650 lm
LED Output:	14 W
Light Yield:	110 lm/W
Light Temperature:	2700, 3000, 4000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<5
Beam Angle:	120 °
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI,Push-Dim
LED-Chip Manufacturer:	MTC
LED-Chip:	SMD 2835
Number of LED:	40
Ignition Time:	<0,5 s
Input Current:	AC 180-264V, 50/60Hz, DC 200-264V
Power Consumption:	15 W
Contains Driver:	✓
Driver Manufacturer:	Boke
Power Factor (PF):	>0.96
Input Driver:	terminal
Output of Driver:	DC 20-40V, 350mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Terminal
Switching Cycles:	>30.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	75x41 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	20 (44 room side)
IK Code:	08
Housing Color	white
Housing Material:	Aluminium+PC
Coating:	lacquered
Special Feature of Housing:	schraubbares Modul
Cover:	opal
Net Weight:	338 g
Type of Packaging:	box
Dimensions of Packaging:	140x140x60
Weight incl. Packaging:	0.4 kg
Content Master Package:	36
Dimensions of Master Package:	575x435x200 mm
Weight Master Package:	12,6 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	54.000 h L80/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE
Barcode:	4250557827445
CCT Select: 2700, 3000, 4000K	
DALI 2 DT6, Push Dim	
elektr. Anschlußdose für Durchgangsverdrahtung	
modulare Aufbau, kombinierbar mit kon.Deckenringen	
1400lm	

Information and Downloads:

