


Artea MKII 23-830/835/840-2300LM CCT-/Power Select Sensor



Technical Details:

Luminous Flux:	2300 lm
LED Output:	22 W
Light Yield:	100 lm/W
Light Temperature:	3000, 3500, 4000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
LED-Chip Manufacturer:	Smalite
LED-Chip:	SMD 2835
Number of LED:	80
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz, DC 180-240V
Power Consumption:	Power Select (7,10,15,23 W)
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	terminal
Output of Driver:	DC 30-50V, 460/300/200/140mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Terminal
Switching Cycles:	>100.000
Electrical Protection Class:	II
Compatible with Emergency Current:	✓
Loop-Through Cabling:	✓

Dimensions:	335x63 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	44
IK Code:	10
Housing Color	white
Housing Material:	Polycarbonat
Special Feature of Housing:	modularer Aufbau
Cover:	opal
Net Weight:	1083 g
Type of Packaging:	box
Dimensions of Packaging:	342x342x70
Weight incl. Packaging:	1.28 kg
Content Master Package:	10
Dimensions of Master Package:	740x370x375 mm
Weight Master Package:	13,99 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405114090
Certifications	CE,TÜV,SELV
Barcode:	4250557826479
Ideal für Flure und Treppenhäuser	
Perfect for corridors and staircase hous	
Kann im Freien unter Vordächer verwendet werden!	
Can be used temporarily outside under canopies	
3CCT Select: 3000-4000K, Power Select: 7,10,15,23W	

Storage Temperature:

-25°C - 55°C

Information and Downloads:

