Product Information

Order number: LG51240

Tridonic Driver LC 25W 700/36 fix SR SNC2



Product information "Tridonic Driver LC 25W 700/36 fix SR SNC2"

LED Constant Current Power Supply

The Tridonic Converter is an extremely versatile power supply for all kinds of LED chips.

Product Features:

- usable for all LED arrays

Product description

- Can be either used built-in or independent with clip-on strain-relief (see accessory)
- Small design (97 x 43 x 30 mm)
- Constant current LED Driver
- For luminaires of protection class I and protection class II
- Temperature protection as per EN 61347-2-13 C5e
- Adjustable output current between 350 and 600 mA, in 5 steps with ADV plug technology (pre-selected current 350 mA)
- Max. output power 26.4 W
- Nominal life-time up to 100,000 h
- 5-year guarantee

Functions

- Overtemperature protection
- Overload protection
- Short-circuit protection
- No-load protection
- Burst protection voltage 1 kV
- Surge protection voltage 1 kV (L to N)
- Surge protection voltage 2 kV (L/N to earth)

Typical applications

Technical Details:

Power Consumption:	25 W
Power Factor (PF):	0.93
Operating Hours:	>50.000 h
Switching Cycles:	>50.000
Ambient Temperature (TA):	-20°C - 50°C
Housing Material:	plastic
Housing Color	white
Warranty	5 years

Information and Downloads:

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

- For panel light and area light in office and education application