


TANEYA 80-840-10400LM DALI/Push-Dim 130lm/W



Technical Details:

Luminous Flux:	10400 lm
Light Yield:	130 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	110x90 °
Unified Glare Rating (UGR):	<13
Light Emission:	
Dimmable:	✓
Method of Dimming:	DALI,Push-Dim
LED-Chip Manufacturer:	Lumileds
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 200- 240V, 50/60Hz
Power Consumption:	80 W
Contains Driver:	✓
Driver Manufacturer:	Boke
Power Factor (PF):	>0.95
Input Driver:	cable with plug
Output of Driver:	DC 24-42V, 1250-2000mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	I

Dimensions:	610x300x2020 mm
Mounting:	ground
IP Class:	20
IK Code:	02
Housing Color	silver
Housing Color (RAL Code):	similar 9006
Housing Material:	aluminum
Coating:	lacquered
Special Feature of Housing:	Steel base
Cover:	prismatic
Net Weight:	12004 g
Type of Packaging:	box
Weight incl. Packaging:	13.89 kg
Content Master Package:	1
Dimensions of Master Package:	910x320x140 mm
Weight Master Package:	13,89 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	60.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,SELV
Barcode:	4250557826646
LSS: B10 18 Leuchten, B16: 20 Leuchten	

Storage Temperature:

-40°C - 60°C

Information and Downloads:



50W up 110° and 30W down 90°

split pole for cost savingcompact transport volume

dreigeteilter Mast für kompaktes Transportmaß