Product Information

Order number: LG32182DA

EGETA 1500 150-840-22500LM Flood DIN 18032-3 UGR<22 DALI 2.0 Dim







Product information "EGETA 1500 150-840-22500LM Flood DIN 18032-3 UGR<22 DALI 2.0 Dim"

Indoor Sporthall luminaire

- Extremly robust Indoor Sporthall light IK10 ball impact resistance DIN 18032-3.
- Elegant white steel housing with prismatic diffusor
- Dali 2.0 or push dimming with power select option: 60-150W / 9000-22500lm
- Easy installtion directly on surfaces with screws. Can be suspended or fixed on ceilings see optional accessories
- Through wireing: 5 x 2,5mm²
- Low glare UGR < 22 (100W - 150W) perfect for many kind of indoor sports
- High efficency: max. 150lm/W
- ball throw protected

Applications:

Sporthall: Hockey, Volleyball, Basketball, Gym, Football, Cricket, Tennis

Technical Details:

Luminous Flux	22500 lm
Light Yield:	150 lm/W
Light Temperature:	4000 K
Color Rendering Index (CRI)	≥80 Ra
Color Consistency (SDCM):	3
Power Consumption:	60, 80, 100, 150 W
Power Factor (PF):	0.9
Operating Hours:	>100.000 h L80/B10
Switching Cycles:	>200.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-20°C - 40°C
Housing Material:	steel
Housing Color	white
Dimensions	1500x348x60 mm
Net Weight:	11800 g
Warranty	5 years

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de