

Order number: LG32182DA

EGETA 1500 150-840-22500LM Flood DIN 18032-3 UGR<22 DALI 2.0 Dim



Technical Details:

Luminous Flux:	22500 lm
Light Yield:	150 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	80 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI,Push-Dim,"Power Select"
LED-Chip Manufacturer:	Juwei 205lm/W
LED-Chip:	SMD2835
Number of LED:	840
Ignition Time:	<0,5 s
Input Current:	AC 200-240V, 50/60Hz, DC 186-250V
Power Consumption:	Power Select (60, 80, 100, 150 W)
Contains Driver:	✓
Driver Manufacturer:	Boke
Power Factor (PF):	>0.9
Input Driver:	terminal
Output of Driver:	DC 100-300V, 200-700mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Terminal
Switching Cycles:	>200.000
Electrical Protection Class:	I

Dimensions:	1500x348x60 mm
Mounting:	Decke,Deckenabhängung
Montageart:	surface mounted
IP Class:	20
IK Code:	10
Housing Color	white
Housing Material:	steel
Special Feature of Housing:	Ballwurfsicher DIN18032-3
Cover:	prismatic
Net Weight:	11800 g
Type of Packaging:	box
Weight incl. Packaging:	16.06 kg
Content Master Package:	1
Dimensions of Master Package:	1670x430x150 mm
Weight Master Package:	16,06 kg
Product Line:	Premio Line
Warranty	5 years
Operating Hours:	100.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405429000
Certifications	CE,LM80
Barcode:	4250557826684
Einfache, und schnelle Montage, In/Out	
Dali 2.0 Push-Dim 1-100% Power Select 9000-22500lm	
Ballwurfsicher nach DIN 18032-3	
Ball impact resistance DIN 18032-3	
Low glare UGR<22, IP20 IK10, RG0	

Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-20°C - 60°C

Information and Downloads:

