Product Information

Order number: LG30816

Ekova UGR 150 26-46/830-865/4500lm max. UGR 19 low Glare, max. 110lm/W BAP







Technical Details:

Luminous Flux	4500 lm
Light Yield:	110 lm/W
Light Temperature:	3000, 4000, 6500 K
Color Rendering Index (CRI)	≥80 Ra
Color Consistency (SDCM):	5
Power Consumption:	26, 32, 40, 46 W
Power Factor (PF):	0.9
Operating Hours:	>50.000 h L80/B20
Switching Cycles:	>50.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-25°C - 45°C
Housing Material:	Polycarbonat
Housing Color	grey
Dimensions	1500x92x70 mm
Net Weight:	1644 g
Warranty	3 years

Information and Downloads:

Product information "Ekova UGR 150 26-46/830-865/4500lm max. UGR 19 low Glare, max. 110lm/W BAP"

IP65 LED damp proof light OneFitAll with low glare rating UGR< 19

Ekova UGR by Litegear® is the perfect dampproof IP65 luminaire for work benches with optimized galre rating. Due to an integrated louver the light distribution angle is limited and optimized for concentraded work on PCs, CNC machines and drive-/walkways Fast amortization with up to 65% electricity savings. Retrova can be mounted as a wall or ceiling light or suspended by means of optional steel cables. Retrova is very robust with IP65 ingress protection and IK08 impact class protection.

OneFitAll Edition with selectable CCT via Switsch on the LED-driver: 3000, 4000, 6500 Kelvin and power select: 26, 32, 40, 46W = Multilumen: 2920, 3400, 4000, 4500 Lumen max. 110lm/W
Easy installtion accessory kits like motion sensor and emergency battery kit as plug and play solution. Any time easy toll free installation!

Applications:
work place, PC station, production, transportation ways

Advantages:

- wire through 3 x 1,5mm² with 2 x terminal 3 pin
- flexible installation brackets and stainless steel clip lockers.
- easy to change light carrier board with electrical terminal with in/out/trough link function
- Low surface temperature below 80°C