

Xona Maxima Value Unit 1416 50-840-9500LM DALI IP54



Technical Details:

Luminous Flux:	9500 lm
LED Output:	70 W
Light Yield:	190 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	90 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI,Push-Dim
LED-Chip Manufacturer:	Ebright
Number of LED:	245
Ignition Time:	<0,5 s
Power Consumption:	Power Select (35, 40, 45, 50 W)
Contains Driver:	✓
Driver Manufacturer:	Litegear
Power Factor (PF):	>0.95
Input Driver:	plug connector
Output of Driver:	DC 120-200V, 275-350mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-25°C - 60°C
Storage Temperature:	-40°C - 85°C

Dimensions:	1426x73x38 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	54
IK Code:	08
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	7-core
Cover:	Lens
Net Weight:	2255 g
Type of Packaging:	box
Weight incl. Packaging:	2.25 kg
Content Master Package:	10
Dimensions of Master Package:	1490*400*230 mm
Weight Master Package:	22 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	70.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,TÜV
Barcode:	4250557827186
IP54 staubgeschütztes Gehäuse	
D Zeichen	
ideal für Produktion, Schreinerei, Landwirtschaft	

