


Spila Square 600-10-830/857-1260LM



Technical Details:

Luminous Flux:	1260 lm
Light Yield:	126 lm/W
Light Temperature:	3000,4000,5700 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	150 °
LED-Chip:	SMD 2835
Ignition Time:	<1 s
Input Current:	AC 200 - 240V, 70mA, 50/60Hz
Power Consumption:	10 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 60°C

Dimensions:	600x61x77,5 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	44
IK Code:	08
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	plastic/Stahl
Special Feature of Housing:	PC mit Schalter
Cover:	opal
Net Weight:	550 g
Type of Packaging:	box
Dimensions of Packaging:	640x95x80
Weight incl. Packaging:	0.7 kg
Content Master Package:	12
Dimensions of Master Package:	650x340x305 mm
Weight Master Package:	9,41 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	94051140
Certifications	CE
Barcode:	4250557825038
Lichtfarbe umschaltbar: 3000K, 4000K, 5700K	
Gehäuse schlagzäh mit Schalter	
Spiegelleuchte mit geringer Blendung	
IEC61000-4-5(L-N:0,5KV)	
1190-1270lm	

Information and Downloads:

