


Spila Square 900-15-830/57-1900LM



Technical Details:

Luminous Flux:	1900 lm
LED Output:	12 W
Light Yield:	127 lm/W
Light Color:	dualwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	150 °
LED-Chip:	SMD 2835
Ignition Time:	<1 s
Input Current:	AC 200 - 240V, 70mA, 50/60Hz
Power Consumption:	15 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 60°C

Dimensions:	900x61x77,5 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	44
IK Code:	08
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	plastic/Stahl
Special Feature of Housing:	PC mit chalter
Cover:	opal
Net Weight:	791 g
Type of Packaging:	box
Weight incl. Packaging:	0.99 kg
Content Master Package:	12
Dimensions of Master Package:	955x340x305 mm
Weight Master Package:	14,5 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	94051140
Certifications	CE
Barcode:	4250557822648
Lichtfarbe umschaltbar:	3000K, 4000K, 5700K
Gehäuse schlagzäh mit Schalter	
Spiegelleuchte mit geringer Blendung	
IEC61000-4-5(L-N:0,5KV)	
1770-1900lm	

Information and Downloads:

