


Cetara Vario MKIV Square 6262 36-830/865-4000LM BAP



Technical Details:

Luminous Flux:	4000 lm
LED Output:	36 W
Light Yield:	122 lm/W
Light Temperature:	3000-6500 K
Light Color:	dualwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	Funk
LED-Chip Manufacturer:	SANAN
LED-Chip:	SMD 4014
Number of LED:	216
Ignition Time:	<0,5 s
Power Consumption:	36 W
Contains Driver:	✓
Driver Manufacturer:	TIGI
Power Factor (PF):	>0.9
Input Driver:	cable with flying leads
Output of Driver:	DC 20-42V, 550-1100mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-30°C - 45°C
Storage Temperature:	-30°C - 80°C

Dimensions:	620x620x9 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	20 (40 room side)
IK Code:	07
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	aluminum
Coating:	powder-coated
Cover:	prismatic
Net Weight:	2420 g
Type of Packaging:	box
Dimensions of Packaging:	655x705x20
Weight incl. Packaging:	3.15 kg
Content Master Package:	5
Dimensions of Master Package:	655x705x20 mm
Weight Master Package:	16,8 kg
Product Line:	Premio Line
Warranty	5 years
Operating Hours:	124.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE
Barcode:	4250557826028
Farbtemperatur: 2700K(warmwhite) - 6500K(kaltwhite)	
mediums Funkfernbedienung veränderbar	
CCT change: from 3000 to 6500 Kelvin with remote	

