

Cetara 6060-36-840-3900LM IP65



Product information "Cetara 6060-36-840-3900LM IP65"

LED Panel damp proof IP65 version

Litegear® Cetara LED panels are made to be installed in to ceilings or to be hung with clips on walls or ropes on ceilings. LED panels have a low power consumption and a long lifespan compared to traditional fluorescent luminaires. With optional hanging kits (a set contains 4 steel wires) the panel can be palced over desks or work areas. Panels create a light flooded atmosphere and look like a skywindow when illuminated. Litegear Cetara LED panels with prismatic cover are perfect to be used for computer desks in offices due to low UGR.A Cetara Panel with 25-36W power consumption can replace a recessed ceiling light with 4 x T8 18W flourescent tubes and can save around 60% energy costs and lower the maintenance costs.

The Litegear LED Panels are available in different dimensions and color temperatures. They look really stylish and have a smooth light output. As an option we offer suitable LED driver in non dimming or dimming version with 1-10V, Dali, DMX, Zigbee or Push dim. Cetara Panels have a very high lumen output.

Cetara Panels have a very high lumen output. up 110lm/W. Special weather proof version IP65. Dust and splash protected.

Applications:

- office, conference room
- shower, in hospital and laboratory, food production, factory
- health care, gym, kitchen



Technical Details:

Luminous Flux	3900 lm
Light Yield:	108 lm/W
Light Temperature:	4000 K
Color Rendering Index (CRI)	≥80 Ra
Color Consistency (SDCM):	4
Power Consumption:	36 W
Power Factor (PF):	0.9
Operating Hours:	>50.000 h L70/B20
Switching Cycles:	>100.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-10°C - 40°C
Housing Material:	aluminum
Housing Color	white
Coating:	powder-coated
Dimensions	595x595x12 mm
Net Weight:	3660 g
Warranty	3 years

Information and Downloads:

