Technical Data Sheet

Order number: LG31463PSHE.2

LITEGEAR
LED Lighting Solutions

Xona Maxima Basic Unit 150FL 55/70-840-13300LM Power Select







Technical Details:

Luminous Flux:	13300 lm
LED Output:	67 W
Light Yield:	190 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<2
Beam Angle:	90 °
Unified Glare Rating (UGR):	<25
Light Emission:	downward
LED-Chip Manufacturer:	Ebright
LED-Chip:	SMD 2835
Number of LED:	345
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 50/60Hz, DC 184-240V
Power Consumption:	Power Select (55, 60, 65, 70 W)
Contains Driver:	✓
Driver Manufacturer:	Litegear
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 100-160V, 260, 320, 380, 440mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-25°C - 50°C

Dimensions:	1499x70x40 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	40
IK Code:	03
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	steel
Coating:	coated
Cover:	clear
Net Weight:	1680 g
Type of Packaging:	box
Weight incl. Packaging:	1.88 kg
Content Master Package:	10
Dimensions of Master Package:	1570x430x210 mm
Weight Master Package:	18,8 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	100.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,TÜV,ENEC,LM80
Barcode:	4250557826004
Power Select: Leistungswahl 55, 60, 65, 70W	
max. 190 Lumen/Watt	
Leuchten pro Leitungsschutzschalter	
B16 8x /C16 12x / A16 7x	
Inrush current: 30AQ180µs Efficiency 93%	

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

Information and Downloads: