Product Information

Order number: LG59074

Lucello UP Multi-CCT BL-Aufbau-Panel 6060-40-830/840-5230LM BAP UGR 19







Product information "Lucello UP Multi-CCT BL-Aufbau-Panel 6060-40-830/840-5230LM BAP UGR 19"

LED Backlight Surface mounting Panel OneFitAll
For computer workstations - suitable according to EN 12464-1 for screens with high luminance!

- elegant slim frame
- Including innovative slim LED driver. Power Select: 33, 36, 40W
- Very low power consumption and high system efficency: >130-140lm/W
- CCT Select: select able light colour by switch on the panel backside: 3000, 3500, 4000 Kelvin
- Replacment for traditional surface troffer lights: 4x 18W T8 flourescent tubes
- excellent price/performance ratio, fast ROI
- Diffusor made from UV stabilized PS
- wide beam angle and very uniform light distribution

Applications:
Shops, corridors, production areas, storage rooms, warehouse, dressing rooms, health club, Fitness, meeting rooms, school

Technical Details:

Luminous Flux	5230 lm
Light Yield:	140 lm/W
Light Temperature:	3000,3500,4000 K
Color Rendering Index (CRI)	≥80 Ra
Color Consistency (SDCM):	3
Power Consumption:	33, 36, 40 W
Power Factor (PF):	0.95
Operating Hours:	>124.000 h L80/B10
Switching Cycles:	>70.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-30°C - 45°C
Housing Material:	steel
Housing Color	white
Coating:	powder-coated
Dimensions	600x600x55 mm
Net Weight:	2795 g
Warranty	5 years

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de