

MODULUX OFFICE Linear LED- Modul 60-18/24-940-3900lm-WH DALI DIM



Technical Details:

Luminous Flux:	3900 lm
Light Yield:	163 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥90 Ra
Color Consistency (SDCM):	<3
Beam Angle:	90 °
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI,Push-Dim
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 200-240V, 50/60Hz
Power Consumption:	Power Select (18,20,22,24 W)
Contains Driver:	✓
Power Factor (PF):	>0.95
Input Driver:	lighting track
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Power rail
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-40°C - 85°C

Dimensions:	600x62x20 mm
Mounting:	Decke,Stromschiene
Montageart:	surface mounted
IP Class:	40
IK Code:	04
Housing Color	white
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	3-Phase adapter
Cover:	Louver
Net Weight:	550 g
Type of Packaging:	none
Content Master Package:	10
Dimensions of Master Package:	670x350x240 mm
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	60.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,TÜV
Spezial Optik für Büro, Showroom, Kassenzone	
Special optics for office, showroom, cashier area	
90° symmetric	
Power adjust: 18/20/22/24W	
Für 3-Phasenstromschien/ for 3 phase trackrail	

Information and Downloads:



