Product Information

Order number: LG32288DABK

MODULUX OFFICE Linear LED- Modul 150-35/50-940-7000lm-BK DALI DIM







Technical Details:

Luminous Flux	7000 lm
Light Yield:	140 lm/W
Light Temperature:	4000 K
Color Rendering Index (CRI)	≥90 Ra
Color Consistency (SDCM):	3
Power Consumption:	35,40,45,50 W
Power Factor (PF):	0.95
Operating Hours:	>100.000 h L80/B50
Switching Cycles:	>100.000
Ignition Time:	<1 s
Ambient Temperature (TA):	-20°C - 60°C
Housing Material:	steel
Housing Color	black
Coating:	powder-coated
Dimensions	1500x62x20 mm
Net Weight:	1700 g
Warranty	5 years

Information and Downloads:

Product information "MODULUX OFFICE Linear LED- Modul 150-35/50-940-7000lm-BK DALI DIM"

Linear LED tracklight for 3-phase trackrails

Elegant, flat LED luminaire with integrated 3-phase track adapter which is completely integrated in the standard track rails. Elegant, ultra flat appearance only 11mm high and 60mm wide. Version with optimized Glare rating UGR< 19 DIN EN 12464-1.
Perfect for office applications, supermarket cashier area, show room, corridors, exhibition

- Easy and fast installation using 3-phase trackrail adapters.
- 3 selectable power phases, compatible with all common track systems
- Adjustment output power select: Adjustable LED driver 35, 40, 45, 50 Watt
- DALI 2.0 Push Dim
- Modular structure of LED louver
- The individual modules can be seamlessly lined up. It creates the impression of a continuous line of light.
- Good heat dissipation and optimal light distribution
- Also available with dimmable Dali 2.0 driver on request.
- Available in 2 housing colors: black, white
- Long-life LED technology: up to 50,000 hours L80 B10