Product Information

Order number: LG51333

Lifud LF-GSD040YG DALI-2 dual white / CW + WW / 2 Ausgänge





Product information "Lifud LF-GSD040YG DALI-2 dual white / CW + WW / 2 Ausgänge"

Dali 2 LED Power Supply

Constant current DC output LED driver with multi level selectable output current by dip switch. DALI-DT8 interface and push dim dimming.
high efficiency up to 84%, with the fanless design for LED indoor lighting

Applications:
LED office lighting
LED architectural lighting
LED panel and downlighting

Features

? DALI or PUSH dimming (logarithmic or linear dimming curve selectable on DALI interface)
? Constant current output and output current adjustable via DIP switch
? Built-in active PFC function
? Standby power consumption < 0.5W
? CCT change: 2700-6500K
? IP20
? Suitable for Class II light fixtures
? 5-year warranty (please refer to the warranty condition)

Technical Details:

Power Consumption:	20 W
Power Factor (PF):	0.9
Operating Hours:	>50.000 h TC<80°C
Switching Cycles:	>100.000
Ambient Temperature (TA):	-30°C - 45°C
Housing Material:	plastic
Housing Color	white
Dimensions	127x81x32 mm
Net Weight:	219 g
Warranty	5 years

Information and Downloads: