Technical Data Sheet


Order number: LG51333

LITEGEAR
LED Lighting Solutions

Lifud LF-GSD040YG DALI-2 dual white / CW + WW / 2 Ausgänge







Technical Details:

Dimmable:	✓
Method of Dimming:	DALI,Push-Dim,DALI-2
Input Current:	AC 220-240V, 300mA, 47/63Hz, DC 310-340V
Power Consumption:	20 W
Driver Manufacturer:	Lifud
Power Factor (PF):	>0.9
Input Driver:	terminal
Output of Driver:	DC 9-42V, 550-1050mA
CC/CV:	CC
Output Current Adjustable:	✓
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-30°C - 45°C
Storage Temperature:	-30°C - 80°C

Dimensions:	127x81x32 mm
Montageart:	surface mounted
IP Class:	20
Housing Color	white
Housing Material:	plastic
Special Feature of Housing:	Selectable output current
Net Weight:	219 g
Type of Packaging:	none
Weight incl. Packaging:	0.244 kg
Content Master Package:	48
Dimensions of Master Package:	385x285x210 mm
Weight Master Package:	11,7 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h TC<80°C
Disposal Obligation:	✓
Customs Tariff Number:	8504408390
Certifications	CE,TÜV,ENEC,SELV
Barcode:	4250557825939
für Panels, Downlights mit Power sowie CCT Select	
Current select: 550-1050 (50 steps)	
DALI DT8 Dual white	

Information and Downloads: