

Order number: LG31471DAHE

Xona Maxima Basic Unit 240SP 70/150-840-28500LM 190lm/W Dali Dim



Technical Details:

Luminous Flux:	28500 lm
LED Output:	150 W
Light Yield:	190 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	30 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI,Push-Dim
LED-Chip Manufacturer:	Ebright
LED-Chip:	SMD 2835
Number of LED:	552
Ignition Time:	<1 s
Input Current:	AC 220-240V, 54-750mA, 50/60Hz, DC 220-240V
Power Consumption:	Power Select (70, 90, 110, 130, 150W W)
Contains Driver:	✓
Driver Manufacturer:	Boke
Power Factor (PF):	>0.98
Input Driver:	terminal
Output of Driver:	DC 220-240V
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I

Dimensions:	2401x69,8x39,4 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	40
IK Code:	03
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	steel
Coating:	coated
Cover:	clear
Net Weight:	2500 g
Type of Packaging:	none
Dimensions of Packaging:	2470x430x210
Weight incl. Packaging:	3 kg
Content Master Package:	10
Dimensions of Master Package:	2470x430x210 mm
Weight Master Package:	28 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,TÜV,ENEC,LM80
Barcode:	4250557827704
Output Select: 70, 90, 110, 130, 150W	
max. 190 Lumen/Watt	
240cm Länge, Alugehäuse	
Dali 2.0 Push Dim	

Ambient Temperature (TA):	-25°C - 60°C
Storage Temperature:	-40°C - 85°C

Information and Downloads:

