


Xona Maxima Basic Unit 240FL 70/150-840-28500LM 190lm/W



Technical Details:

Luminous Flux:	28500 lm
Light Yield:	190 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	90 °
Unified Glare Rating (UGR):	<25
Light Emission:	downward
LED-Chip Manufacturer:	Epistar
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 170 - 264V, 50/60Hz, DC 170-230V
Power Consumption:	Power Select (70, 90, 110, 130, 150 W)
Contains Driver:	✓
Driver Manufacturer:	Litegear
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 55-80V
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-20°C - 55°C

Dimensions:	2399x70x39,4 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	40
IK Code:	02
Housing Color	white
Housing Material:	steel
Coating:	coated
Cover:	clear
Net Weight:	1780 g
Type of Packaging:	none
Content Master Package:	10
Dimensions of Master Package:	2450x390x210 mm
Weight Master Package:	38 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,TÜV,ENEC,LM80
Output Select: 70, 90, 110, 130, 150W	
max. 190 Lumen/Watt	
240cm Länge, Alugehäuse	

