
Technical Data Sheet

Order number: LG51336

Lifud ADD009-0200-42 Dali 2





Technical Details:

Dimmable:	✓
Method of Dimming:	DALI,Push-Dim
Input Current:	AC 220 - 240V, 47/63Hz
Power Consumption:	Power Select (4, 6, 8, 9 W)
Driver Manufacturer:	Lifud
Power Factor (PF):	>0.9
Input Driver:	terminal
Output of Driver:	DC 9-42V, 100, 150, 180,200mA
CC/CV:	CC
Output Current Adjustable:	✓
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 60°C

Dimensions:	142x30x22 mm
Montageart:	surface mounted
IP Class:	20
Housing Color	white
Housing Material:	plastic
Special Feature of Housing:	Selectable output current
Net Weight:	67 g
Type of Packaging:	none
Content Master Package:	96
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h TC<70°C
Disposal Obligation:	✓
Customs Tariff Number:	8504408390
Certifications	CE,TÜV,ENEC,SELV
ideal für Panels und Downlights	
Current select: 100, 150, 180, 200	

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de