Technical Data Sheet

Order number: LG11131


LITEGEAR
LED Lighting Solutions

Lunara Clou 120-200/830-850-30000lm BEG 150lm/W max.









Technical Details:

Luminous Flux:	30000 lm
Light Yield:	150 lm/W
Light Temperature:	3000, 4000, 5000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	150x80 °
Light Emission:	
Dimmable:	✓
Method of Dimming:	0-10V,PWM,Poti
LED-Chip Manufacturer:	Shineon
LED-Chip:	SMD3030
Number of LED:	360
Ignition Time:	<0,5 s
Input Current:	AC 120-277V, 0,25-1mA, 50/60Hz
Power Consumption:	Power Select (120, 150, 200 W)
Contains Driver:	✓
Driver Manufacturer:	Sosen
Power Factor (PF):	>0.95
Input Driver:	cable with flying leads
Output of Driver:	DC 150-280V
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	cable with flying leads
Switching Cycles:	>200.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-40°C - 50°C

Dimensions:	353x384x59 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
Pivot Range tilt:	180 °
IP Class:	66 (66 room side)
IK Code:	08
Housing Color	dunkel silvergrey
Housing Color (RAL Code):	similar 9006
Housing Material:	aluminum
Coating:	powder-coated
Cover:	clear
Net Weight:	3700 g
Type of Packaging:	box
Dimensions of Packaging:	450x400x93
Weight incl. Packaging:	4.55 kg
Content Master Package:	1
Dimensions of Master Package:	455x410x95 mm
Weight Master Package:	4,55 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	100.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,LM80
Barcode:	4250557827599

High System Efficency: 140-150 Lumen/Watt

Dimmable 0-10V + 12V 0,2A DC Aux out

max. 150lm/W BEG förderfähig

Anschlußterminal 5 polig

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

Information and Downloads:

