

VARIA-FLEX Stromschienenstrahlertubus max. 32W



Technical Details:

Swappable Reflector:	✓
Output of Driver:	DC 30-42V
CC/CV:	CC
Input Lamp:	Terminal
Ambient Temperature (TA):	-10°C - 45°C
Storage Temperature:	-20°C - 60°C

Information and Downloads:



Dimensions:	206x85x211 mm
Mounting:	Decke, Stromschiene
Montageart:	surface mounted
Pivot Range pan:	350 °
Pivot Range tilt:	90 °
IP Class:	20
Housing Color	white
Housing Color (RAL Code):	similar 9003
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	for 3-Phase Track Adapter
Net Weight:	818 g
Type of Packaging:	box
Weight incl. Packaging:	0.96 kg
Content Master Package:	12
Dimensions of Master Package:	540x410x300 mm
Weight Master Package:	12,27 kg
Product Line:	Advance Line
Warranty	5 years
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE, LM80
Barcode:	4250557826271
Gehäuse zur Aufnahme von LED-Modul, Linse, Treiber	
housing to carry LED module, lens and driver	