

# RETROVA EXTREME EM 1570 55-840-865-9750LM 185lm/W max.



## Technical Details:

Luminous Flux:	9750 lm
Light Yield:	185 lm/W
Light Temperature:	4000, 5000, 6500 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Unified Glare Rating (UGR):	<30
Light Emission:	downward
LED-Chip Manufacturer:	Jufei
LED-Chip:	SMD 2835 0,5W
Number of LED:	313
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 320mA, 50/60Hz
Power Consumption:	Power Select (31-55W W)
Contains Driver:	✓
Driver Manufacturer:	Philips Xitanium
Power Factor (PF):	>0.9
Input Driver:	terminal
Output of Driver:	DC 120-185V, 200-350mA
Output Current Adjustable:	✓
Input Lamp:	Terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-25°C - 50°C

Dimensions:	1570x85x80 mm
Mounting:	Decke,Wand,Deckenabhängung
Montageart:	surface mounted
IP Class:	66
IK Code:	08
Housing Color	hellgrey
Housing Material:	Polycarbonat
Special Feature of Housing:	Edelstahl Clips UV-stabil
Cover:	prismatic
Net Weight:	1623 g
Type of Packaging:	box
Weight incl. Packaging:	2.13 kg
Content Master Package:	8
Dimensions of Master Package:	1625x360x195 mm
Weight Master Package:	17,5 kg
Product Line:	Premio Line
Warranty	5 years
Operating Hours:	70.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,ENEC,SELV,HACCP
Barcode:	4250557827384
UV stable housing, Efficiency: 94%	
Anzahl Leuchten:10B: 13,16B: 20, 10C: 19, 16C: 30	
Max. 185lm/W @ 5000K sonst 170-175lm/W	

Information and Downloads:

