
Technical Data Sheet


Order number: LG59077

LITEGEAR
LED Lighting Solutions

Lucello Advance Multi-CCT BL-Panel 6262-34-930/940-5150LM BAP UGR<19 HI CRI 150-165lm/W







Technical Details:

Luminous Flux:	5150 lm
Light Yield:	165 lm/W
Light Temperature:	3000,3500,4000 K
Light Color:	CCT Select
Color Rendering Index:	≥90 Ra
Color Consistency (SDCM):	<3
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD2835
Ignition Time:	<0,5 s
Input Current:	AC 200-240V, 170mA, 50/60Hz
Power Consumption:	Power Select (20-34 W)
Driver Manufacturer:	AGT
Power Factor (PF):	>0.9
Input Driver:	cable with flying leads
Output of Driver:	DC 30-38V, 500-900mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	plug connector
Switching Cycles:	>50.000
Electrical Protection Class:	II
Loop-Through Cabling:	✓
Ambient Temperature (TA):	-30°C - 45°C
Storage Temperature:	-40°C - 80°C

Dimensions:	620x620x40 mm
Cut-Out Dimensions:	600x600 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	20 (44 room side)
IK Code:	04
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	steel
Coating:	lacquered
Cover:	prismatic
Net Weight:	1840 g
Type of Packaging:	box
Dimensions of Packaging:	650x650x40
Weight incl. Packaging:	2.36 kg
Content Master Package:	5
Dimensions of Master Package:	665x50x695 mm
Weight Master Package:	12,86 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	100.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE
Barcode:	4250557827612
Bildschirmarbeitsplatz tauglich nach EN 12464-1	
CCT-Select: schaltbare Lichtfarbe 3000,3500,4000K	
Power Select: 20-34W Treiber einstellbar	
Backlite Technology 150-160lm/W	

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

