

# Artea MKII 23-830/835/840-2300LM CCT-/Power Select



## Product information "Artea MKII 23-830/835/840-2300LM CCT-/Power Select"

Universal surface-mounted luminaire

Artea is a universal wall / ceiling mounted luminaire with CCT Select 3000/3500/4000K and Power Select: function output power 7, 10, 15, 23W and luminous flux: 700, 1000, 1500 and 2300 lumens. Artea has a service friendly, modular design. LED board and driver are combined on a replaceable unit. Optionally, a battery supply can be additionally connected for autonomous emergency power operation. The luminaire has a robust, impact-resistant plastic housing which can also be used in protected outdoor areas. Maximum 42 luminaires can be operated by a 16A fuse breaker.

Can be used as slave luminaire in combination with Sensor Master luminaire.

Optional with battery emergency kit



### Technical Details:

Luminous Flux	2300 lm
Light Yield:	100 lm/W
Light Temperature:	3000, 3500, 4000 K
Color Rendering Index (CRI)	≥80 Ra
Color Consistency (SDCM):	3
Power Consumption:	7,10,15,23 W
Power Factor (PF):	0.9
Operating Hours:	>50.000 h L80/B20
Switching Cycles:	>100.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-25°C - 40°C
Housing Material:	Polycarbonat
Housing Color	white
Dimensions	335x63 mm
Warranty	5 years

Information and Downloads:

