


Artea 23-830/840-2300LM CCT-/Power Select, Sensor + Emergency Autotest



Technical Details:

| | |
|------------------------------|---|
| Luminous Flux: | 2300 lm |
| LED Output: | 20 W |
| Light Yield: | 100 lm/W |
| Light Temperature: | 3000,3500,4000 K |
| Light Color: | CCT Select |
| Color Rendering Index: | ≥80 Ra |
| Color Consistency (SDCM): | <3 |
| Beam Angle: | 120 ° |
| Unified Glare Rating (UGR): | <19 |
| Light Emission: | downward |
| LED-Chip Manufacturer: | Smalite |
| LED-Chip: | SMD 2835 |
| Number of LED: | 80 |
| Ignition Time: | <0,5 s |
| Input Current: | AC 220 - 240V, 140-460mA, 50/60Hz, DC 180-240 |
| Power Consumption: | Power Select (7,10,15,23 W) |
| Contains Driver: | ✓ |
| Power Factor (PF): | >0.9 |
| Input Driver: | terminal |
| Output of Driver: | DC 30-50V, 140-460mA |
| CC/CV: | CC |
| Output Current Adjustable: | ✓ |
| Input Lamp: | Terminal |
| Switching Cycles: | >100.000 |
| Electrical Protection Class: | I |
| Loop-Through Cabling: | ✓ |
| Ambient Temperature (TA): | 0°C - 40°C |
| Storage Temperature: | -20°C - 40°C |

| | |
|-------------------------------------|--|
| Dimensions: | 335x63 mm |
| Mounting: | ceiling,wall |
| Montageart: | surface mounted |
| IP Class: | 44 (44 room side) |
| IK Code: | 10 |
| Housing Color | white |
| Housing Color (RAL Code): | similar 9016 |
| Housing Material: | plastic |
| Special Feature of Housing: | modularer Aufbau |
| Cover: | opal |
| Net Weight: | 1500 g |
| Luminaire Type: | Fluchtwegleuchtung |
| Testing Facility: | automatischer Selbsttest |
| Battery Warranty: | 3 |
| Discharge Duration: | ≥3 h |
| Battery Type: | LiFePo4 |
| Battery Current: | 1800 mA |
| Battery Charge Duration: | 24 h |
| Initial Charge Duration: | 24 h |
| Charging Power Consumption: | 1.5 W |
| Luminous Flux in Battery Mode: | 270 lm |
| Standards for emergency luminaires: | DIN EN 60598-2-22, DIN EN 62034: 2012, Anforderung nach DIN EN 50172 |
| Type of Packaging: | box |
| Dimensions of Packaging: | 343x343x70 |
| Weight incl. Packaging: | 1.6 kg |
| Content Master Package: | 10 |
| Dimensions of Master | 745x360x365 mm |



| | |
|--|------------------|
| Product Line: | Advance Line |
| Warranty | 5 years |
| Operating Hours: | 50.000 h L80/B20 |
| Disposal Obligation: | ✓ |
| Customs Tariff Number: | 9405114090 |
| Certifications | CE |
| Barcode: | 4250557827247 |
| Ideal für Flure/Treppenhäuser, Batterienotlicht 3h | |
| Perfect for corridors/staircase hous, emergency 3h | |
| Microwave Sensor Version, Master/Slave Mode | |
| Can be used temporarily outside under canopies | |
| 3CCT Select: 3000-4000K,Power Select: 7,10,15,23W | |