

# Allestra MKII 30/60-727/740-9600LM IP66 IK08 0-10V PWM Dim



## Technical Details:

Luminous Flux	9600 lm
Light Yield:	160 lm/W
Light Temperature:	2700, 3000, 4000 K
Color Rendering Index (CRI)	≥70 Ra
Color Consistency (SDCM):	5
Power Consumption:	30, 45, 60 W
Power Factor (PF):	0.95
Operating Hours:	>100.000 h L70/B50
Switching Cycles:	>100.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-40°C - 50°C
Housing Material:	aluminum
Housing Color	grey
Coating:	lacquered
Dimensions	450x246x122 mm
Net Weight:	4100 g
Warranty	5 years

## Product information "Allestra MKII 30/60-727/740-9600LM IP66 IK08 0-10V PWM Dim"

LED Street Light OneFitAll® concept

- Litegear® Allestra is a versatile LED streetlight with PWM 0-10V dimming interface, Zhags socket for Sesnors and wireless adapters.
- Build in SDP 10KV surge protection
- Selectable CCT: 2700K, 3200K, 4000K
- Power Select: 30W, 45W, 60W
- It can be used on roads or parking areas. It is highly efficient up to 160lm/W with interchangeable lens modules. Due to its long lifespan maintenance cost will decrease dramatically. Due to its low power consumption and long lifespan users will have a quick return on investment.
- Nice sleek, modular design guarantees an excellently performing product with very low dust accumulation.
- ENEC certified

Information and Downloads:



factory buildings.

The ideal installation height is 4 - 10 meters. It can be mounted on all poles with 60/76mm tube dimensions due to integrated reduction adapter to 60mm dimension. Polemount adapter can be adjusted from 0-90 degree.