


Order number: LG59077DA

Lucello Advance Multi-CCT BL-Panel 6262-34-930/940-5150LM BAP UGR<19 HI CRI 145-160lm/W DALI DT6 Push Dim



Technical Details:

Luminous Flux:	5150 lm
Light Yield:	160 lm/W
Light Temperature:	3000,3500,4000 K
Light Color:	CCT Select
Color Rendering Index:	≥90 Ra
Color Consistency (SDCM):	<3
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI,Push-Dim
LED-Chip Manufacturer:	San'an
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 170mA, 50/60Hz
Power Consumption:	Power Select (21-34 W)
Contains Driver:	✓
Driver Manufacturer:	AGT
Power Factor (PF):	>0.9
Input Driver:	terminal
Output of Driver:	DC 9-40V, 300-1050mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	plug connector
Switching Cycles:	>50.000
Electrical Protection Class:	II
Loop-Through Cabling:	✓
Ambient Temperature (TA):	-30°C - 45°C
Storage Temperature:	-40°C - 80°C

Dimensions:	620x620x34 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	20 (20 room side)
IK Code:	04
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	steel
Coating:	lacquered
Cover:	prismatic
Net Weight:	2000 g
Type of Packaging:	box
Dimensions of Packaging:	650x45x690
Weight incl. Packaging:	2.5 kg
Content Master Package:	5
Dimensions of Master Package:	650x45x690 mm
Weight Master Package:	13,6 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	100.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE
Barcode:	4250557827629
Bildschirmarbeitsplatz tauglich nach EN 12464-1	
CCT-Select: schaltbare Lichtfarbe 3000,3500,4000K	
Power Select: DALI DT2 20-34W Treiber einstellbar	
Backlite Technology 150-160lm/W	
OneFitAll Push Dim	

