
Technical Data Sheet

**Order number: LG14394WH**

LITEGEAR
LED Lighting Solutions

# DURATA Advance 40-830/840-4800LM UP/DOWN UGR DALI 2 DIM










## Technical Details:

| | |
|---|---|
| **Luminous Flux:** | 4800 lm |
| **LED Output:** | 35.6 W |
| **Light Yield:** | 120 lm/W |
| **Light Temperature:** | 3000, 3500, 4000 K |
| **Light Color:** | CCT Select |
| **Color Rendering Index:** | ≥80 Ra |
| **Color Consistency (SDCM):** | <3 |
| **Unified Glare Rating (UGR):** | <19 |
| **Light Emission:** | |
| **Dimmable:** | ✓ |
| **Method of Dimming:** | DALI,Push-Dim |
| **LED-Chip Manufacturer:** | San'an |
| **LED-Chip:** | SMD 2835 |
| **Number of LED:** | 840 |
| **Ignition Time:** | <0,5 s |
| **Input Current:** | AC 200-240V, 1050mA, 50/60Hz, DC 176-280V |
| **Power Consumption:** | 40 W |
| **Contains Driver:** | ✓ |
| **Driver Manufacturer:** | Eaglerise |
| **Power Factor (PF):** | >0.95 |
| **Input Driver:** | plug connector |
| **Output of Driver:** | DC 15-51V, 1000mA |
| **CC/CV:** | CC |
| **Output Current Adjustable:** | ✓ |
| **Input Lamp:** | plug connector |
| **Switching Cycles:** | >30.000 |
| **Electrical Protection Class:** | I |
| **Compatible with Emergency Current:** | ✓ |
| **Loop-Through Cabling:** | ✓ |

| | |
|---|---|
| **Dimensions:** | 1500x50x100 mm |
| **Mounting:** | Decke |
| **Montageart:** | surface mounted |
| **IP Class:** | 20 (20 room side) |
| **IK Code:** | 05 |
| **Housing Color** | white |
| **Housing Color (RAL Code):** | similar 9016 |
| **Housing Material:** | aluminum |
| **Coating:** | powder-coated |
| **Special Feature of Housing:** | Interconnectable |
| **Cover:** | prismatic |
| **Net Weight:** | 3000 g |
| **Type of Packaging:** | box |
| **Dimensions of Packaging:** | 1555x60x110 |
| **Weight incl. Packaging:** | 3.79 kg |
| **Content Master Package:** | 6 |
| **Dimensions of Master Package:** | 1570x200x255 mm |
| **Weight Master Package:** | 19 kg |
| **Product Line:** | Advance Line |
| **Warranty** | 5 years |
| **Operating Hours:** | 50.000 h L80/B20 |
| **Disposal Obligation:** | ✓ |
| **Customs Tariff Number:** | 9405499090 |
| **Certifications** | CE |
| **Barcode:** | 4250557827315 |
| Elegante, modulare Lichtlinienleuchte für Büros | |
| Dali 2 Dim CCT Select 3000, 3500, 4000K | |
| Zuleitung nicht enthalten | |
| 3600lm direkt,1200lm indirekt | |

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

| | |
|---|---|
| **Storage Temperature:** | -40°C - 80°C |

Information and Downloads: