

DURATA Advance 40-830/840-4800LM UP/DOWN UGR DALI DIM



Technical Details:

| | |
|------------------------------|-----------------------------|
| Luminous Flux: | 4800 lm |
| LED Output: | 84 W |
| Light Yield: | 120 lm/W |
| Light Temperature: | 3000, 3500, 4000 K |
| Light Color: | CCT Select |
| Color Rendering Index: | ≥80 Ra |
| Color Consistency (SDCM): | <3 |
| Unified Glare Rating (UGR): | <19 |
| Light Emission: | |
| Dimmable: | ✓ |
| Method of Dimming: | DALI, Push-Dim |
| LED-Chip Manufacturer: | San'an |
| LED-Chip: | SMD 2835 |
| Number of LED: | 840 |
| Ignition Time: | <0,5 s |
| Input Current: | AC 200-240V, 200mA, 50/60Hz |
| Power Consumption: | 40 W |
| Contains Driver: | ✓ |
| Driver Manufacturer: | Boke |
| Power Factor (PF): | >0.95 |
| Input Driver: | plug connector |
| Output of Driver: | DC 24-42V, 1000mA |
| CC/CV: | CC |
| Output Current Adjustable: | ✓ |
| Input Lamp: | plug connector |
| Switching Cycles: | >100.000 |
| Electrical Protection Class: | I |
| Ambient Temperature (TA): | -25°C - 35°C |
| Storage Temperature: | -40°C - 80°C |

| | |
|-------------------------------------------------|-------------------|
| Dimensions: | 1500x50x100 mm |
| Mounting: | Decke |
| Montageart: | surface mounted |
| IP Class: | 20 (20 room side) |
| IK Code: | 05 |
| Housing Color | white |
| Housing Color (RAL Code): | similar 9016 |
| Housing Material: | aluminum |
| Coating: | powder-coated |
| Special Feature of Housing: | Interconnectable |
| Cover: | prismatic |
| Net Weight: | 3420 g |
| Type of Packaging: | box |
| Dimensions of Packaging: | 1555x60x110 |
| Weight incl. Packaging: | 3.79 kg |
| Content Master Package: | 6 |
| Dimensions of Master Package: | 1570x200x255 mm |
| Weight Master Package: | 19 kg |
| Product Line: | Advance Line |
| Warranty | 5 years |
| Operating Hours: | 60.000 h L80/B10 |
| Disposal Obligation: | ✓ |
| Customs Tariff Number: | 9405429000 |
| Certifications | CE |
| Barcode: | 4250557827315 |
| Elegante, modulare Lichtlinienleuchte für Büros | |
| Dali 2 Dim CCT Select 3000, 3500, 4000K | |
| Zuleitung nicht enthalten | |
| 3600lm direkt, 1200lmindirekt | |

